





WILLIAMS - AMBER A135 CABINET

SPECIFICATION DETAILS A135

External Dimensions (w x d x h - mm) 606x577x805

Internal Dimensions (w x d x h - mm) 536x434x606

Door opening 606

Capacity cu.ft/ltrs 4.8/135

KEY FEATURES

- · Stainless steel exterior with aluminium interior
- Self closing doors on A400 mode
- Barrel locked doors
- Magnetic balloon door gaskets with 100% tight seal
- Fitted with nylon coated, adjustable wire shelves on refrigerator models and static shelves on freezers.
- Pilaster racking with removable shelving clips on high temp models
- Removable racking system on high temp models
- Precision injected, high density polyurethane insulation with low GWP (Global Warming Potential) and zero ODP (Ozone Depletion Potential)
- Front vented refrigeration system (A135 and A280)
- CoolSmart controller
- Designed and engineered to operate efficiently up to 32°C ambient
- Air cooled condensing unit
- Defrost water is vaporised using recycled heat from compressor (high temp only)
- High performance helium leak testing

OPTIONS

- Additional shelves / clips (high temp only)
- 50mm castors
- Interior light (high temp only)
- · Left hand hung doo





AMBER A135 CABINET TECHNICAL DATA

SPECIFICATION DETAILS	HA135	LA135
SPECIFICATION DETAILS	HA135	LA135
Temperature (°C)	+1/+4°C	-18/-22°C
Climate Class	Class 4 (30°C)	Class 4 (30°C)
Power Supply	230V/50Hz/1Ph	230V/50Hz/1Ph
Fuse (Amps)	13	13
Defrost	Automatic Off Cycle	Manual
Noise level (dBA)	55	44
Shelves	2	2
Trayslides per section	-	Fixed
ELECTRICAL/ENERGY DATA		
Refrigerant	R600A	R290
Energy Efficiency Class	А	-
Energy Consumption (kW / 24hrs)	0.85	-
Start Up (Amps)	3.7	7.7
Running (Amps)	0.53	1.3
Heat Rejection	194	300

