

SERVICELINE

Catering & Refrigeration Equipment Sales  Est. 1989



**WILLIAMS GARNET
G1 CABINET**

WILLIAMS - GARNET G1 CABINET

SPECIFICATION DETAILS

G1

External Dimensions (w x d x h - mm)	727x824x1960
Internal Dimensions (w x d x h - mm)	567 x 665 x 1411
Door opening	567
Capacity cu.ft/ltrs	21.9/620

***Heated Garnet has an increased width of 737mm**

KEY FEATURES

- Foodsafe stainless steel exterior and interior
- Radiused, easy clean, interior based corners
- Self closing doors
- Barrel locked doors
- Magnetic balloon door gaskets with 100% tight seal
- Fitted with 4 of 2/1GN nylon coated wire shelves per section as standard or trayslides to accommodate 2/1GN containers
- Anti-tilt trayslides
- Removable racking system
- Precision injected, high density 80mm polyurethane insulation with low GWP (Global Warming Potential) and zero ODP (Ozone Depletion Potential).
- Heavy duty, non-marking swivel castors with brakes
- Top mounted removable refrigeration system
- CoolSmart controller
- Designed and engineered to operate efficiently up to 43°C ambient
- Fully automatic air cooled condensing unit
- Defrost water is vaporised using recycled heat from compressor
- High performance helium leak testing

OPTIONS

- Aluminium interior
- Additional shelving / trayslides
- Left hand door hang
- Adjustable legs in lieu of castors (add 10mm to height)
- Non-hydrocarbon version available (excluding Freezers)

GARNET G1 CABINET TECHNICAL DATA

SPECIFICATION DETAILS	HG1T	MG1T	LG1T	CFG1T	FG1T	XG1T
Temperature (°C)	+1/+4°C	-2/+2°C	18/-22°C	0/+3°C	-2/+2°C	+78/+83°C
Climate Class	Class 4 (30°C)	-	Class 4 (30°C)	Class 4 (30°C)	-	-
Power Supply	230V /50Hz/1Ph	230V /50Hz/1Ph	230V /50Hz/1Ph	230V /50Hz/1Ph	230V /50Hz/1Ph	230V /50Hz/1Ph
Fuse (Amps)	13	13	13	13	13	13
Defrost	Automatic Off Cycle	Automatic Electric	Automatic Electric	Automatic Off Cycle	Automatic Off Cycle	-
Noise level (dBA)	59	59	61	59	58	-
Shelves	4	4	4	4	8	4
Trayslides per section	8	8	8	8	16	8
ELECTRICAL/ENERGY DATA - STANDARD REFRIGERANT						
Refrigerant	R134a	R134a	-	R134a	R134a	-
Energy Efficiency Class	C	-	-	C	-	-
Energy Consumption (kW / 24hrs)	1.69	-	-	1.69	-	-
Start Up (Amps)	9.6	9.6	-	9.6	10.7	12
Running (Amps)	2.06	2.06	-	2.06	3	11.5
Heat Rejection	407	407	-	407	565	-
ELECTRICAL/ENERGY DATA - HYDROCARBON REFRIGERANT						
Refrigerant	R290	R290	R290	R290	R290	-
Energy Efficiency Class	C	-	D	C	-	-
Energy Consumption (kW / 24hrs)	1.42	-	5.65	1.42	-	-
Start Up (Amps)	9.5	9.5	16.6	9.5	12.6	-
Running (Amps)	1.64	1.64	2.8	1.64	1.93	-
Heat Rejection	484	484	623	484	710	-

SERVICELINE

Catering & Refrigeration Equipment Sales  Est. 1989



01438 363 040

ServiceLine 1 Icen Ct, Icknield Way, Letchworth Garden City SG6 1TN