


SERVICELINE

Catering & Refrigeration Equipment Sales  Est. 1989



**WILLIAMS J2 JADE
REFRIDGERATED CABINET**

WILLIAMS - JADE J2 REFRIGERATED CABINET

SPECIFICATION DETAILS	HJ2/MJ2/LJ2
External Dimensions (w x d x h - mm)	727 x 824 x 1960
Internal Dimensions (w x d x h - mm)	567 x 665 x 1411
Door opening	567
Capacity cu.ft/ltrs	21.9/620

KEY FEATURES

- Foodsafe stainless steel exterior and aluminium interior**
- Full length integral 'easy grab' door handle
- Radiused, easy clean, interior based corners
- Self closing doors
- Barrel locked doors
- Magnetic balloon door gaskets with 100% tight seal
- J1, J2 and J500 units are fitted with 3 of 2/1GN nylon coated wire shelves per section as standard or trayslides to accommodate 2/1GN containers
- Anti-tilt trayslides
- Removable racking system
- Precision injected, high density 80mm polyurethane insulation with low GWP (Global Warming Potential) and zero ODP (Ozone Depletion Potential)
- Heavy duty, non-marking swivel castors with brakes
- CoolSmart controller
- Designed and engineered to operate efficiently up to 43°C ambient
- Air cooled condensing unit
- Defrost water is vaporised using recycled heat from compressor

OPTIONS

- Stainless steel interior
- Additional shelving / trayslides
- Left hand door hang
- Adjustable legs in lieu of castors (add 10mm to height, 40mm to the J300U/ J400U)
- Non-hydrocarbon version available (excluding Freezers)

JADE J2 CABINET TECHNICAL DATA

SPECIFICATION DETAILS	HJ2	MJ2	LJ2
Temperature (°C)	+1/+4°C	-2/+2°C	-18/-22°C
Climate Class	Class 4 (30°C)	-	Class 4 (30°C)
Power Supply	230V/50Hz/1Ph	230V/50Hz/1Ph	230V/50Hz/1Ph
Fuse (Amps)	13	13	13
Defrost	Automatic off cycle	Automatic Electric	Automatic Electric
Noise level (dBA)	65	65	70
Refrigeration System	Top mounted	Top mounted	Top mounted
Shelves	6	6	6
Trayslides per section	6	6	6
ELECTRICAL/ENERGY DATA - STANDARD REFRIGERANT			
Refrigerant	R134a	R134a	-
Energy Efficiency Class	D	-	-
Energy Consumption (kW / 24hrs)	3.29	-	-
Start Up (Amps)	13.7	13.7	-
Running (Amps)	2.81	2.81	-
Heat Rejection	710	710	-
ELECTRICAL/ENERGY DATA - HYDROCARBON REFRIGERANT			
Refrigerant	R290	R290	R290
Energy Efficiency Class	C	-	D
Energy Consumption (kW / 24hrs)	3.31	-	10.61
Start Up (Amps)	13.5	13.5	13.5
Running (Amps)	1.42	1.42	3.36
Heat Rejection	768	769	1068

SERVICELINE

Catering & Refrigeration Equipment Sales  Est. 1989



01438 363 040

ServiceLine 1 Icen Ct, Icknield Way, Letchworth Garden City SG6 1TN