

# SERVICELINE

Catering & Refrigeration Equipment Sales  Est. 1989



**WILLIAMS J300U JADE  
REFRIDGERATED CABINET**

## WILLIAMS - JADE J300U REFRIGERATED CABINET

### SPECIFICATION DETAILS

### J300U

External Dimensions (w x d x h - mm)	727 x 824 x 1960
Internal Dimensions (w x d x h - mm)	567 x 665 x 1411
Door opening	567
Capacity cu.ft/ltrs	21.9/620

### KEY FEATURES

- Foodsafe stainless steel exterior and aluminium interior\*\*
- Full length integral 'easy grab' door handle
- Radiused, easy clean, interior based corners
- Self closing doors
- Barrel locked doors
- Magnetic balloon door gaskets with 100% tight seal
- J1, J2 and J500 units are fitted with 3 of 2/1GN nylon coated wire shelves per section as standard or trayslides to accommodate 2/1GN containers
- Anti-tilt trayslides
- Removable racking system
- Precision injected, high density 80mm polyurethane insulation with low GWP (Global Warming Potential) and zero ODP (Ozone Depletion Potential)
- Heavy duty, non-marking swivel castors with brakes
- CoolSmart controller
- Designed and engineered to operate efficiently up to 43°C ambient
- Air cooled condensing unit
- Defrost water is vaporised using recycled heat from compressor

### OPTIONS

- Stainless steel interior
- Additional shelving / trayslides
- Left hand door hang
- Adjustable legs in lieu of castors (add 10mm to height, 40mm to the J300U/ J400U)
- Non-hydrocarbon version available (excluding Freezers)

## JADE J300U CABINET TECHNICAL DATA

SPECIFICATION DETAILS	HJ300U	LJ300U
Temperature (°C)	+1/+4°C	-18/-22°C
Climate Class	Class 4 (30°C)	Class 4 (30°C)
Power Supply	230V/50Hz/1Ph	230V/50Hz/1Ph
Fuse (Amps)	13	13
Defrost	Automatic off cycle	Automatic off cycle
Noise level (dBA)	63	61
Refrigeration System	Bottom Mounted	Bottom Mounted
Shelves	3	3
Trayslides per section	6	6
<b>ELECTRICAL/ENERGY DATA - STANDARD REFRIGERANT</b>		
Refrigerant	R134a	-
Energy Efficiency Class	C	-
Energy Consumption (kW / 24hrs)	1.29	-
Start Up (Amps)	9.6	-
Running (Amps)	1.72	-
Heat Rejection	407	-
<b>ELECTRICAL/ENERGY DATA - HYDROCARBON REFRIGERANT</b>		
Refrigerant	R290	R290
Energy Efficiency Class	C	D
Energy Consumption (kW / 24hrs)	1.25	4.82
Start Up (Amps)	9.5	9.5
Running (Amps)	1.7	1.7
Heat Rejection	484	623

# SERVICELINE

Catering & Refrigeration Equipment Sales  Est. 1989



01438 363 040

ServiceLine 1 Icen Ct, Icknield Way, Letchworth Garden City SG6 1TN