





WILLIAMS - MAR1 MEAT AGEING REFRIGERATOR

SPECIFICATION DETAILS MAR1

External Dimensions (w x d x h - mm) 727 x 824 x 1960

Internal Dimensions (w x d x h - mm) 567 x 665 x 1411

Door opening 567

Capacity cu.ft/ltrs 21.9/620

KEY FEATURES

- Ideal operating temperature of +1 to +6°C and humidity between 60-90%
- CoolSmart controller
- Humidity display
- Foodsafe stainless steel exterior and interio
- Robust, full length, stainless steel door handle
- Radiused, easy clean, interior based corners
- Self closing glass door
- Barrel locked door
- Heavy duty, magnetic balloon door gasket with 100% tight seal
- Anti-tilt trayslides
- 4 of 2/1GN perforated stainless steel shelves. Load capacity maximum 20kg per shelf.
- Removable racking system
- Internal bright, low heat, LED full height strip lighting
- Himalayan salt blocks to assist with moisture management and
- Precision injected, high density 80mm polyurethane insulation with low GWP (Global Warming Potential) and zero ODP (Ozon Depletion Potential)
- Heavy duty, non-marking swivel castors with brakes
- Natural hydrocarbon refrigerant
- Designed and engineered to operate efficiently up to 43°C
- Air cooled condensing unit
- Defrost water is vaporised using recycled heat from compressor
- High performance helium leak testing

OPTIONS

- Two robust meat hanging rails: maximum load of 40kg per rail
- Removable waste catch pans
- Additional shelving / travslides
- Left hand door hand
- Available in various colours / textures Stainless steel back

IMPORTANT NOTES

*Energy consumption is tested to EN16825 in 24hrs (MRC16 only)

***Heat rejection is evaporating at -10°C in 32°C Ambien

Williams is committed to a policy of continual product development and innovation. As such, williams reserve the right to change product specifications stated without prior notice.





MAR1 - MEAT AGEING REFRIGERATOR TECHNICAL DATA

SPECIFICATION DETAILS	MAR1
Temperature (°C)	+1/+6°C
Climate Class	Class 5 (40°C)
Power Supply	230V/50Hz/1Ph
Fuse (Amps)	13
Defrost	Automatic Off Cycle
Noise level (dBA)	63
Refrigeration System	Top Mounted
Shelves	4
Trayslides per section	8
ELECTRICAL/ENERGY DATA	
Refrigerant	R290
Energy Efficiency Class	N/A
Energy Consumption (kW / 24hrs)	N/A
Start Up (Amps)	9.5
Running (Amps)	1.65
Heat Rejection	484

