

# SERVICELINE

Catering & Refrigeration Equipment Sales  Est. 1989



**WILLIAMS - OPAL  
O2U - TWO DOOR COUNTER**

## WILLIAMS - 02U OPAL TWO DOOR COUNTER

SPECIFICATION DETAILS	02U
External Dimensions (w x d x h - mm)	1400 x 700 x 857
Internal Dimensions (w x d x h - mm)	870 x 585 x 600
Door opening	390
Capacity cu.ft./ltrs	13.2/374

### KEY FEATURES

- Foodsafe stainless steel exterior and interior
- Radiused, easy clean, interior based corners
- Self closing doors
- Barrel locked doors
- Removable refrigeration cassette system for easy servicing
- Magnetic balloon door gaskets with 100% tight seal
- Fitted with 2 1/1GN nylon coated wire shelves per section as standard or trayslides to accommodate 1/1GN containers
- Anti-tilt trayslides
- Removable racking system
- Precision injected, high density polyurethane insulation with Low GWP (Global Warming Potential) and zero ODP (Ozone Depletion Potential)
- Heavy duty, non-marking swivel castors with brakes
- CoolSmart controller
- Designed and engineered to operate efficiently up to a 43°C ambient
- Fully automatic air cooled condensing unit
- Defrost water is vaporised using recycled heat from compressor
- High performance helium leak testing
- Audio and visual hi/lo temp alarm
- Condenser cleaning light to indicate when cleaning required

### OPTIONS

- Stainless steel back
- Additional shelving / trayslides
- Drawer banks (2 or 3)
- Raised pan holder
- Wells - Full/standard/special
- Hinged cover
- Integral or Screw on splash-back
- Adjustable legs in lieu of castors (add 10mm)
- Reverse unit
- Non-hydrocarbon version available (excluding Freezers)
- Helicoil cable

### IMPORTANT NOTES

\*Energy consumption is tested to EN16825 in 24hrs

\*\*Heat rejection is evaporating at -10°C in 32°C Ambient

All refrigeration equipment requires adequate ventilation for efficient and effective performance

Williams is committed to a policy of continual product development and innovation. As such, we reserve the right to change product specifications stated without prior notice.

## O2U - OPAL 2 DOOR COUNTER TECHNICAL DATA

SPECIFICATION DETAILS	H02U	M02U	L02U	F02U
Temperature (°C)	+1/+4°C	-2/+2°C	-18/-22°C	-2/+2°C
Climate Class	Class 4 (30°C)	-	Class 4 (30°C)	-
Power Supply	230V/50Hz/1Ph	230V/50Hz/1Ph	230V/50Hz/1Ph	230V/50Hz/1Ph
Fuse (Amps)	13	13	13	13
Defrost	Automatic Off Cycle	Automatic Electric	Automatic Hot Gas	Automatic Off Cycle
Noise level (dBA)	63	63	61	63
Shelves	4	4	4	-
Trayslides per section	4	4	4	-
<b>ELECTRICAL/ENERGY DATA - STANDARD REFRIGERANT</b>				
Refrigerant	R134a	R134a	-	R134a
Energy Efficiency Class	A	-	-	-
Energy Consumption (kW / 24hrs)	1.44	-	-	-
Start Up (Amps)	9.6	9.6	-	11.5
Running (Amps)	1.77	1.77	-	2.9
Heat Rejection	407	407	-	527
<b>ELECTRICAL/ENERGY DATA - HYDROCARBON REFRIGERANT</b>				
Refrigerant	R290	R290	R290	-
Energy Efficiency Class	A	-	D	-
Energy Consumption (kW / 24hrs)	1.43	-	5.63	-
Start Up (Amps)	9.5	9.5	14.2	-
Running (Amps)	1.68	1.68	2.58	-
Heat Rejection	484	484	623	-

# SERVICELINE

Catering & Refrigeration Equipment Sales  Est. 1989



01438 363 040

ServiceLine 1 Icen Ct, Icknield Way, Letchworth Garden City SG6 1TN