

SERVICELINE

Catering & Refrigeration Equipment Sales  Est. 1989



**WILLIAMS - OPAL
O4U - FOUR DOOR COUNTER**

WILLIAMS - 04U

OPAL FOUR DOOR COUNTER

SPECIFICATION DETAILS	04U
External Dimensions (w x d x h - mm)	2360 x 700 x 857
Internal Dimensions (w x d x h - mm)	1830 x 585 x 600
Door opening	390
Capacity cu.ft./ltrs	25.3/715

KEY FEATURES

- Foodsafe stainless steel exterior and interior
- Radiused, easy clean, interior based corners
- Self closing doors
- Barrel locked doors
- Removable refrigeration cassette system for easy servicing
- Magnetic balloon door gaskets with 100% tight seal
- Fitted with 2 1/1GN nylon coated wire shelves per section as standard or trayslides to accommodate 1/1GN containers
- Anti-tilt trayslides
- Removable racking system
- Precision injected, high density polyurethane insulation with Low GWP (Global Warming Potential) and zero ODP (Ozone Depletion Potential)
- Heavy duty, non-marking swivel castors with brakes
- CoolSmart controller
- Designed and engineered to operate efficiently up to a 43°C ambient
- Fully automatic air cooled condensing unit
- Defrost water is vaporised using recycled heat from compressor
- High performance helium leak testing
- Audio and visual hi/lo temp alarm
- Condenser cleaning light to indicate when cleaning required

OPTIONS

- Stainless steel back
- Additional shelving / trayslides
- Drawer banks (2 or 3)
- Raised pan holder
- Wells - Full/standard/special
- Hinged cover
- Integral or Screw on splash-back
- Adjustable legs in lieu of castors (add 10mm)
- Reverse unit
- Non-hydrocarbon version available (excluding Freezers)
- Helicoil cable

IMPORTANT NOTES

*Energy consumption is tested to EN16825 in 24hrs

**Heat rejection is evaporating at -10°C in 32°C Ambient

All refrigeration equipment requires adequate ventilation for efficient and effective performance

Williams is committed to a policy of continual product development and innovation. As such, we reserve the right to change product specifications stated without prior notice.

O4U - OPAL 4 DOOR COUNTER TECHNICAL DATA

SPECIFICATION DETAILS

H04U

Temperature (°C)	+1/+4°C
Climate Class	Class 4 (30°C)
Power Supply	230V/50Hz/1Ph
Fuse (Amps)	13
Defrost	Automatic Off Cycle
Noise level (dBA)	63
Shelves	8
Trayslides per section	4

ELECTRICAL/ENERGY DATA - STANDARD REFRIGERANT

Refrigerant	R134a
Energy Efficiency Class	C
Energy Consumption (kW / 24hrs)	2.75
Start Up (Amps)	9.6
Running (Amps)	1.77
Heat Rejection	407

ELECTRICAL/ENERGY DATA - HYDROCARBON REFRIGERANT

Refrigerant	R290
Energy Efficiency Class	B
Energy Consumption (kW / 24hrs)	2.60
Start Up (Amps)	9.5
Running (Amps)	1.68
Heat Rejection	484

SERVICELINE

Catering & Refrigeration Equipment Sales  Est. 1989



01438 363 040

ServiceLine 1 Icen Ct, Icknield Way, Letchworth Garden City SG6 1TN