

SERVICELINE

Catering & Refrigeration Equipment Sales  Est. 1989



**WILLIAMS - JADE
JC3 - THREE DOOR COUNTER**

WILLIAMS - JC3 JADE THREE DOOR COUNTER

SPECIFICATION DETAILS	JC3
External Dimensions (w x d x h - mm)	1880 x 700 x 857
Internal Dimensions (w x d x h - mm)	1350 x 585 x 600
Door opening	390
Capacity cu.ft/ltrs	19.2/545

KEY FEATURES

- Foodsafe stainless steel exterior and aluminium interior
- Radiused, easy clean, interior based corners
- Self closing doors
- Barrel locked doors
- Magnetic balloon door gaskets with 100% tight seal
- Fitted with 2 of 1/1GN nylon coated wire shelves per section as standard or trayslides to accommodate 1/1GN containers
- Anti-tilt trayslides
- Removable racking system
- Precision injected, high density polyurethane insulation with low GWP (Global Warming Potential) and zero ODP (Ozone Depletion Potential).
- Heavy duty, non-marking swivel castors with brakes
- Removable refrigeration system designed for easy service and maintenance
- CoolSmart controller
- Designed and engineered to operate efficiently up to a 43°C ambient
- Fully automatic air cooled condensing unit
- Defrost water is vaporised using recycled heat from compressor
- High performance helium leak testing

OPTIONS

- Slimline 2 and 3 models available - depth of just 500mm - see separate datasheet
- Stainless steel interior
- Additional shelving / trayslides
- Drawer banks (2 or 3) refer to page 3 for configurations available
- Raised pan holder
- Screw on splash-back
- Adjustable legs in lieu of castors (add 10mm)
- Non-hydrocarbon versions available (Excluding Freezers)
- Wells - full / standard / special

IMPORTANT NOTES

*Energy consumption is tested to EN16825 in 24hrs

**Heat rejection is evaporating at -10°C in 32°C Ambient

All refrigeration equipment requires adequate ventilation for efficient and effective performance

Williams is committed to a policy of continual product development and innovation. As such, williams reserve the right to change product specifications stated without prior notice.

JC3 - JADE THREE DOOR COUNTER TECHNICAL DATA

SPECIFICATION DETAILS	HJC3	MJC3	LJC3
Temperature (°C)	+1/+4°C	-2/+2°C	-18/-22°C
Climate Class	Class 4 (30°C)	-	Class 4 (30°C)
Power Supply	230V/50Hz/1Ph	230V/50Hz/1Ph	230V/50Hz/1Ph
Fuse (Amps)	13	13	13
Defrost	Automatic Off Cycle	Automatic Electric	Automatic Hot Gas
Noise level (dBA)	63	63	61
Shelves	6	6	6
Trayslides per section	4	4	4
ELECTRICAL/ENERGY DATA - STANDARD REFRIGERANT			
Refrigerant	R134a	R134a	-
Energy Efficiency Class	B	-	-
Energy Consumption (kW / 24hrs)	2.11	-	-
Start Up (Amps)	9.6	9.6	-
Running (Amps)	1.77	1.77	-
Heat Rejection	407	407	-
ELECTRICAL/ENERGY DATA - HYDROCARBON REFRIGERANT			
Refrigerant	R290	R290	R290
Energy Efficiency Class	B	-	D
Energy Consumption (kW / 24hrs)	2.00	-	7.23
Start Up (Amps)	9.5	9.5	14.2
Running (Amps)	1.68	1.68	2.58
Heat Rejection	484	484	623

SERVICELINE

Catering & Refrigeration Equipment Sales  Est. 1989



01438 363 040

ServiceLine 1 Icen Ct, Icknield Way, Letchworth Garden City SG6 1TN